TECHNICAL TRAINING

MINIMUM AND MAXIMUM INFORMATION



6mm glass toughened only

The minimum size we can manufacture in toughened glass must have one-dimension exceeding 250mm. If both the height and width are less than 250mm the glass cannot be toughened and will need to be made in annealed or laminated glass.

- Any unit over 1400mm in both directions must be made in 6mm glass. Anything more than 1300mm in both directions should use a minimum of a 12mm cavity.
- Any unit over 2.90m2 must be made in 6mm glass.

Annealed or laminated glass only

- The maximum unit weight we can manufacture is 114kg and has a maximum size limit of 3.80m2 or 2.53m2 in triple.
- Any unit over 1900mm in both directions cannot be manufactured by Glass Systems.
- Patterned glass comes in stock sheets of 1320 x 2140mm. The only patterned glass available above this size is satin. 6mm patterned glass is only available in: Autumn, Cotswold, Everglade, Flemish, Stippolyte and Satin.
- Glass sheets are 3210mm in width, so we cannot manufacture a unit with either dimension more than 3210mm.

4mm glass annealed or toughened

The table below is a guide to our minimum and maximum size units and the glass thickness. Please check your exact glazing size with the criteria detailed above and ensure that any legislative or legal guidance is adhered to when specifying. On larger units in 4mm, flex is possible, so 6mm should be considered if required, although again flex may be evident.

	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200
100	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.10	0.11	0.12	0.13	0.14	0.15	0.16	0.17	0.18	0.19	0.20												
200	0.02	0.04	0.06	0.08	0.10	0.12	0.14	0.16	0.18	0.20	0.22	0.24	0.26	0.28	0.30	0.32	0.34	0.36	0.38	0.40	0.42	0.44	0.46									
300	0.03	0.06	0.09	0.12	0.15	0.18	0.21	0.24	0.27	0.30	0.33	0.36	0.39	0.42	0.45	0.48	0.51	0.54	0.57	0.60	0.63	0.66	0.69	0.72	0.75	0.78						
400	0.04	0.08	0.12	0.16	0.20	0.24	0.28	0.32	0.36	0.40	0.44	0.48	0.52	0.56	0.60	0.64	0.68	0.72	0.76	0.80	0.84	0.88	0.92	0.96	1.00	1.04	1.08	1.12	1.16			
500	0.05	0.10	0.15	0.20	0.25	0.30	0.35	0.40	0.45	0.50	0.55	0.60	0.65	0.70	0.75	0.80	0.85	0.90	0.95	1.00	1.05	1.10	1.15	1.20	1.25	1.30	1.35	1.40	1.45	1.50	1.55	1.60
600	0.06	0.12	0.18	0.24	0.30	0.36	0.42	0.48	0.54	0.60	0.66	0.72	0.78	0.84	0.90	0.96	1.02	1.08	1.14	1.20	1.26	1.32	1.38	1.44	1.50	1.56	1.62	1.68	1.74	1.80	1.86	1.92
700	0.07	0.14	0.21	0.28	0.35	0.42	0.49	0.56	0.63	0.70	0.77	0.84	0.91	0.98	1.05	1.12	1.19	1.26	1.33	1.40	1.47	1.54	1.61	1.68	1.75	1.82	1.89	1.96	2.03	2.10	2.17	2.24
800	0.08	0.16	0.24	0.32	0.40	0.48	0.56	0.64	0.72	0.80	0.88	0.96	1.04	1.12	1.20	1.28	1.36	1.44	1.52	1.60	1.68	1.76	1.84	1.92	2.00	2.08	2.16	2.24	2.32	2.40	2.48	2.56
900	0.09	0.18	0.27	0.36	0.45	0.54	0.63	0.72	0.81	0.90	0.99	1.08	1.17	1.26	1.35	1.44	1.53	1.62	1.71	1.80	1.89	1.98	2.07	2.16	2.25	2.34	2.43	2.52	2.61	2.70	2.79	2.88
1000	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.70	1.80	1.90	2.00	2.10	2.20	2.30	2.40	2.50	2.60	2.70	2.80	2.90	3.00	3.10	3.20
1100	0.11	0.22	0.33	0.44	0.55	0.66	0.77	0.88	0.99	1.10	1.21	1.32	1.43	1.54	1.65	1.76	1.87	1.98	2.09	2.20	2.31	2.42	2.53	2.64	2.75	2.86	2.97	3.08	3.19	3.30	3.41	3.52
1200	0.12	0.24	0.36	0.48	0.60	0.72	0.84	0.96	1.08	1.20	1.32	1.44	1.56	1.68	1.80	1.92	2.04	2.16	2.28	2.40	2.52	2.64	2.76	2.88	3.00	3.12	3.24	3.36	3.48	3.60	3.72	
1300	0.13	0.26	0.39	0.52	0.65	0.78	0.91	1.04	1.17	1.30	1.43	1.56	1.69	1.82	1.95	2.08	2.21	2.34	2.47	2.60	2.73	2.86	2.99	3.12	3.25	3.38	3.51	3.64	3.77			
1400	0.14	0.28	0.42	0.56	0.70	0.84	0.98	1.12	1.26	1.40	1.54	1.68	1.82	1.96	2.10	2.24	2.38	2.52	2.66	2.80	2.94	3.08	3.22	3.36	3.50	3.64	3.78					
1500	0.15	0.30	0.45	0.60	0.75	0.90	1.05	1.20	1.35	1.50	1.65	1.80	1.95	2.10	2.25	2.40	2.55	2.70	2.85	3.00	3.15	3.30	3.45	3.60	3.75							
1600	0.16	0.32	0.48	0.64	0.80	0.96	1.12	1.28	1.44	1.60	1.76	1.92	2.08	2.24	2.40	2.56	2.72	2.88	3.04	3.20	3.36	3.52	3.68									
1700	0.17	0.34	0.51	0.68	0.85	1.02	1.19	1.36	1.53	1.70	1.87	2.04	2.21	2.38	2.55	2.72	2.89	3.06	3.23	3.40	3.57	3.74										
1800	0.18	0.36	0.54	0.72	0.90	1.08	1.26	1.44	1.62	1.80	1.98	2.16	2.34	2.52	2.70	2.88	3.06	3.24	3.42	3.60	3.78											
1900	0.19	0.38	0.57	0.76	0.95	1.14	1.33	1.52	1.71	1.90	2.09	2.28	2.47	2.66	2.85	3.04	3.23	3.42	3.61	3.80												

4mm glass toughened only